

This header space is for local jurisdiction to put their own logo and information

High Efficiency Interior Lighting System Form

Permit No.: _____ Jurisdiction: _____

Site Address: _____

Subdivision/Lot: _____ and/or

Map and Tax Lot: _____

By my signature below, I certify that the above mentioned building has been installed in accordance with Oregon Residential Specialty Code N1107.2^[1] and N1107.3^[2]

Signature : _____ Date: _____
Owner/General Contractor/Authorized Agent

Print Name: _____

^[1]**Section N1107.2 High-efficacy lamps.** All permanently installed lighting fixtures shall contain high-efficacy lamps. Screw-in compact fluorescent and LED lamps comply with this requirement. The building official shall be notified in writing at the final inspection that the permanently installed lighting fixtures have met this requirement. Exception: Two permanently installed lighting fixtures are not required to have high-efficacy lamps. ^[2]**Section N1107.3 High-efficacy exterior lighting.** All exterior lighting fixtures affixed to the exterior of the building shall contain high-efficacy lamps. Exception: Two permanently installed lighting fixtures are not required to have high-efficacy lamps.

Moisture Sensitive Wood Framing Moisture Content Form

I, _____, am the general contractor or the owner/builder at the following address:

Street Address _____

City _____ State _____ Zip Code _____

Permit No.: _____ Jurisdiction: _____

Subdivision/Lot: _____ and/or Map and Tax Lot: _____

To conform with the 2017 Oregon Residential Specialty Code (ORSC), Section R318.2, I am notifying the building official that I am aware of the moisture content requirement of ORSC Section R318.2 and have taken steps to meet this code requirement.

Signature : _____ Date: _____
Owner/General Contractor/Authorized Agent

Print Name: _____

Section R318.2 Moisture content. Prior to the installation of interior finishes, the building official shall be notified in writing by the general contractor that all moisture-sensitive wood framing members used in construction have a moisture content of not more than 19 percent of the weight of dry wood framing members.